



# ACOUSTIC **AQUASTOP** gold

Material : IXPE 20-L / 2,0 mm IXPE foam with PE foil /

Parameter	Value	Quantity
<b>Thickness</b>	<b>2,0</b>	<b>[mm]</b>
Length	15	[m]
<b>Width</b>	<b>1</b>	<b>[m]</b>
Density	33	[kg/m <sup>3</sup> ]
<b>Reflected walking sound reduction</b>	<b>17</b>	<b>[%]</b>
Impact sound reduction	18	[dB]
<b>Compressive strength</b>	<b>100</b>	<b>[kPa]</b>
Weight	0,11	[kg/m <sup>2</sup> ]
<b>Thermal insulation</b>	<b>0,04</b>	<b>[m<sup>2</sup>K/W]</b>
Moisture barrier	> 75	[m]
<b>Reaction to fire</b>	<b>Efl</b>	
Punctual conformability	1,0	[mm]
<b>HS</b>	<b>39211900</b>	




Floor heating



**YES**

Thermal insulation



0,040 m<sup>2</sup>K/W

Impact sound reduction



18 dB

Reflected walking sound reduction




17%

Moisture barrier




>75

Compressive strength



100 kPa/m<sup>2</sup>

Punctual Conformability



1 mm

Healthiness



SGS  
SHAEC120625  
5201

Recycling



**YES**

THE BEST FLOORING UNDERLAYS

